

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
23 June 2005 (23.06.2005)


PCT

(10) International Publication Number  
**WO 2005/056144 A2**

- (51) International Patent Classification<sup>7</sup>: **A63K 3/02**
- (21) International Application Number:  
PCT/DK2004/000863
- (22) International Filing Date:  
14 December 2004 (14.12.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
DKPA200301856  
15 December 2003 (15.12.2003) DK  
DKPA200400232  
16 February 2004 (16.02.2004) DK  
DKPA200400679 30 April 2004 (30.04.2004) DK
- (71) Applicant (for all designated States except US): **VIRK-LUND SPORT A/S** [DK/DK]; Korshøjvej 2, DK-8600 Silkeborg (DK).
- (72) Inventor; and  
(75) Inventor/Applicant (for US only): **CHRISTENSEN, Poul** [DK/DK]; Nordhøjen 13, Himmelev, DK-4000 Roskilde (DK).
- (74) Agent: **AWAPATENT A/S**; Tegholm Allé 13, DK-2450 Copenhagen SV (DK).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: A STARTING BLOCK



(57) Abstract: The present invention relates to a starting block (1) for athletic running. Said starting block comprises an elongated frame (2) having a longitudinal axis, which extends between a first end (3) and a second end (4) of the frame (2), said frame (2) being adapted to be attached to a ground in both ends of the frame (2), at least one take-off block (8, 9) to be arranged in connection with said frame (2), the take-off block (8, 9) comprises a take-off surface (10). The starting block is characterised in that the take-off surface (10) is angularly adjustable in a laterally direction in relation to the longitudinal axis of the frame (2).



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declarations under Rule 4.17:**

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ,*

*NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)*

- *of inventorship (Rule 4.17(iv)) for US only*

**Published:**

- *without international search report and to be republished upon receipt of that report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*